

TC 50 series

Polyamide filler plug



TC 50 GENERAL INFORMATION

Technical data

Filler and Drain Plugs

Polyamide filler plug

TC50 is a range of plastic compact air breathers and filler plugs for protection of the tank against the solid contamination contained into the air and filling of the fluid into the systems during the commissioning and maintenance procedures.

They are directly fitted on the tank.

Available features:

- G 1" male threaded connection, with or without nut
- Metal filtration, to hold the coarse contamination contained into the air
- Filling basket, to hold the coarse contamination contained into the fluid and to diffuse the fluid flow into the tank
- Caps with different graphics and colours, for the use in several applications

Common applications:

- Hydraulic systems
- Mobile machines
- Industrial equipment

Materials

- Cover: Polyamide
- Filter element: Galvanized steel
- Filler cap: Polyamide
- Strainer: Galvanized steel / Polyamide AISI 304 / Polyamide
- Collar: Polyamide
- Seals: Inorganic fibre
- Ringnut: Phosphatized steel

Temperature

From -25 °C to +100 °C

Weight

TC 50 G1" conn. 0.70 kg TC 50 with ringnut 0.10 kg

Quantity

25 pcs/pack



Designation & Ordering code


	COI	MPLETE FILLER PI	LUG							
Serie	s	Configuration example :	TC50	G1	L90	Р	R	0	C70	P01
TC50		-								
Conn	astions	I								
G1	ections G 1"									
GA	With ringnut	-								
		•								
	tion rating									
L90	Galvanized steel									
Seals		I								
P	Inorganic fiber									
	•	-								
Cove	r colour									
R	Red									
Y	Yellow									
Cove	r wording	l								
0	Oil									
N	Neutral	-								
		-								
Bask										
S	Without basket	-								
C70	With basket 70 mm - galvanized steel	=				III	ecution		_	
170	With basket 70 mm - AISI 304	=				PO		Filtri s	tandard	
						Px		stomize		


66

Dimensions

TC50


Threaded connection





TC50

With ringnut



Through hole on the tank

